

The make4ht build system

Michal Hoftich*

Version v0.2g
2019-05-24

Contents

1	Introduction	2
1.1	How it works	2
1.1.1	The issues with default tex4ht conversion commands	2
2	Output file formats and extensions	4
2.1	Extensions	4
3	Build files	5
3.1	User commands	5
3.1.1	Provided commands	5
3.1.2	Command function	5
3.1.3	Parameters table	6
3.1.4	Repetition	7
3.1.5	Expected exit code	7
3.2	File matches	7
3.2.1	Filters	7
3.2.2	DOM filters	9
3.2.3	make4ht-aeneas-config package	9
3.3	Image conversion	11
3.4	The mode variable	12
3.5	The settings table	12
3.6	List of available settings for filters and extensions.	13
3.6.1	The tidy extension	13
3.6.2	The fixinlines dom filter	13
3.6.3	The joincharacters dom filter	14
3.6.4	The mathjaxnode filter	14
3.6.5	The aeneas filter	14
3.6.6	The staticsite filter and extension	15
3.6.7	The dvisvgm_hashes extension	15

*michal.h21@gmail.com

3.6.8	The odttemplate filter and extension	16
4	Configuration file	16
4.1	Location	16
4.2	Additional commands	16
4.3	Example	16
5	Command line options	16
6	Troubleshooting	17
6.1	Incorrect handling of command line arguments for tex4ht, t4ht or latex	17
6.2	Filenames containing spaces	18
6.3	Filenames containing non-ASCII characters	18
7	License	18
8	Changelog	18

1 Introduction

make4ht is a simple build system for tex4ht, \TeX to XML converter. It provides a command line tool that drive the conversion process. It also provides a library which can be used to create customized conversion tools. An example of such conversion tool is tex4ebook for conversion of \TeX to ePub and other e-book formats.

1.1 How it works

1.1.1 The issues with default tex4ht conversion commands

tex4ht system supports several output formats, most notably XHTML, HTML 5 and ODT. The conversion can be invoked using several commands. These commands invoke LaTeX or Plain TeX with special instructions to load tex4ht.sty package. The \TeX run produces special DVI file which contains the code for desired output format. Produced DVI file is then processed and desired output files are created.

The basic command provided by tex4ht is named htlatex. It compiles \LaTeX files to HTML with this command sequence:

```
latex $latex_options 'code for loading tex4ht.sty \input{filename}'
latex $latex_options 'code for loading tex4ht.sty \input{filename}'
latex $latex_options 'code for loading tex4ht.sty \input{filename}'
tex4ht $tex4ht_options filename
t4ht $t4ht_options filename
```

The options for various parts of the system can be passed on the command line:

```
htlathex filename "tex4ht.sty options" "tex4ht_options" "t4ht_options" "latex_options"
```

For basic HTML conversion it is possible to use the most basic invocation:

```
htlathex filename.tex
```

It can be much more involved for HTML 5 output in UTF-8 encoding:

```
htlathex filename.tex "xhtml,html5,charset=utf-8" "-cmozhtf -utf8"
```

make4ht can simplify it:

```
make4ht -uf html5 filename.tex
```

Another issue is the fixed compilation order and hard-coded number of LaTeX invocations.

When you need to run a program which interact with LaTeX, such as Makeindex or Bibtex, you need to create a new script based on htlathex, or run htlathex twice, which means that LaTeX will be invoked six times. This can lead to significantly long compilation times. make4ht provides build files and extensions, which can be used for interaction with external tools.

It is also possible to have several compilation modes. When you just add new text to a document, which doesn't contain cross-references, don't add new stuff to the table of contents, etc., it is possible to use the draft mode which will invoke LaTeX only once. It can save quite a lot of the compilation time:

```
make4ht -um draft -f html5 filename.tex
```

There are also issues with a behaviour of the t4ht application. It reads file filename.lg, generated by tex4ht, where are instructions about generated files, CSS instructions, calls to external applications, instructions for image conversions etc. It can be instructed to copy generated files to some output directory, but it doesn't preserve directory structure, so when you have images in a subdirectory, they will be copied to the output directory. Links will be pointing to a non-existing subdirectory. The following command should copy all output files to the correct destinations.

```
make4ht -d outputdir filename.tex
```

The image conversion is configured in the env file, which has really strange syntax based and the rules are os dependent. make4ht provides simpler means for the image conversion in the build files.

With make4ht build files, we have simple mean to fix these issues. We can change image conversion parameters without the need to modify the env file, or execute actions on the output files. These actions can be either external programs such as xslt processors or HTML tidy or Lua functions.

The idea is to make system controlled by a build file. Because Lua interpreter is included in modern TeX distributions and Lua is ideal language for such task, it was chosen as language in which the build scripts are written.

2 Output file formats and extensions

The default output format used by make4ht is html5. Different format can be requested using the `--format` option. Supported formats are:

- xhtml
- html5
- odt
- tei
- docbook

The `--format` option can be also used for extension loading.

2.1 Extensions

Extensions can be used to modify the build process without the need to use a build file. They may post-process the output files or request additional commands for the compilation.

The extensions can be enabled or disabled by appending `+EXTENSION` or `-EXTENSION` after the output format name:

```
make4ht -uf html5+tidy filename.tex
```

Available extensions:

latexmk_build use Latexmk for \LaTeX compilation.

tidy clean the HTML files using the tidy command.

dvisvgm_hashes efficient generation of SVG pictures using Dvisvgm. It can utilize multiple processor cores and generates only changed images.

common_filters clean the output HTML files using filters.

common_domfilters clean the HTML file using DOM filters. It is more powerful than `common_filters`. Used DOM filters are `fixinlines`, `idcolons` and `joincharacters`.

join_colors load the `joincolors` domfilter for all HTML files.

mathjaxnode use `mathjax-node-page` to convert from MathML code to HTML + CSS or SVG. See the available settings.

odttemplate automatically load the `odttemplate` filter.

staticsite build the document in form suitable for static site generators like Jekyll.

3 Build files

make4ht supports build files. These are Lua scripts which can adjust the build process. You can request external applications like bibtex or makeindex, pass options to the commands, modify the image conversion process, or post-process the generated files.

make4ht tries to load default build file named as filename + .mk4 extension. You can choose different build file with -e or --build-file command line option.

Sample build file:

```
Make:htlatex()
Make:match("html$", "tidy -m -xml -utf8 -q -i ${filename}")
```

Make:htlatex() is preconfigured command for calling LaTeX with tex4ht loaded on the input file. In this case, it will be called one time. After compilation, the tidy command is executed on the output HTML file.

Note that you don't have to call tex4ht and t4ht commands explicitly in the build file, they are called automatically.

3.1 User commands

You can add more commands like Make:htlatex using Make:add command:

```
Make:add("name", "command", {parameters}, repetition)
```

The name and command parameters are required, rest of the parameters are optional.

This defines name command, which can be then executed as Make:name() command.

3.1.1 Provided commands

Make:htlatex One call to TeX engine with special configuration for tex4ht loading.

Make:latexmk Use Latexmk for the document compilation. tex4ht will be loaded automatically.

Make:tex4ht Process the DVI file and creates the output files.

Make:t4ht Creates the CSS file.

3.1.2 Command function

The command parameter can be either string template or function:

```
Make:add("text", "echo hello, input file: ${input}")
Make:add("function", function(params)
  for k, v in pairs(params) do
```

```

    print(k..": ".v)
  end, {custom="Hello world"}
)

```

The template can get variable value from the parameters table using a `${var_name}` placeholder. Templates are executed using operating system, so they should invoke existing OS commands. Function commands may execute system commands using `os.execute` function.

3.1.3 Parameters table

`parameters` parameter is optional, it can be table or nil value, which should be used if you want to use the repetition parameter, but don't want to modify the parameters table.

The table with default parameters is passed to all commands, they can be accessed from command functions or templates. When you specify your own parameters in the command definition, these additional parameters are added to the default parameters table for this particular command. You can override the default parameters in the parameters table.

The default parameters are following:

htlatex used compiler

input it is output file name in fact

tex_file input TeX file

latex_par parameters to latex

packages insert additional LaTeX code which is inserted before `\documentclass`.
Useful for passing options to packages or additional packages loading

tex4ht_sty_par parameters to `tex4ht.sty`

tex4ht_par parameters to the `tex4ht` application

t4ht_par parameters to the `t4ht` application

outdir the output directory

repetition limit number of command execution.

correct_exit expected exit code from the command. The compilation will be terminated if the command exit code is different.

3.1.4 Repetition

Repetition is number which specifies a maximal number of executions of the particular command. This is used for instance for `tex4ht` and `t4ht` commands, as they should be executed only once in the compilation. They would be executed multiple times if you include them in the build file because they are called by `make4ht` by default. Because these commands allow only one repetition, the second execution will be blocked.

3.1.5 Expected exit code

You can set the expected exit code from a command with a `correct_exit` key in the parameters table. The compilation will be stopped when the command returns a different exit code.

This mechanism isn't used for LaTeX (for all TeX engines and formats, in fact), because it doesn't differentiate between fatal and non-fatal errors, and it returns the same exit code in all cases. Log parsing is used because of that, error code 1 is returned in the case of fatal error, 0 is used otherwise. The `Make.testlogfile` function can be used in the build file to detect compilation errors in the TeX log file.

3.2 File matches

Another type of action which can be specified in the build file is `match`. It can be called on the generated files:

```
Make:match("html$", "tidy -m -xml -utf8 -q -i ${filename}")
```

It tests output file names with Lua pattern matching and on matched items will execute a command or a function, specified in the second argument. Commands may be specified as strings, the templates will be expanded, `${var_name}` placeholders will be replaced with corresponding variables from the parameters table, described in the previous subsection. One additional variable is available: `filename`. It contains the name of the current output file.

The above example will clean all output HTML files using the `tidy` command.

If function is used instead, it will get two parameters. The first one is a current filename, the second one table with parameters.

3.2.1 Filters

Some default match actions which can be used are available from the `make4ht-filter` module. It contains some functions which are useful for fixing some `tex4ht` bugs or shortcomings.

Example:

```
local filter = require "make4ht-filter"  
local process = filter{"cleanspan", "fixligatures", "hruletohr"}
```

```
Make:htlatex()
Make:htlatex()
Make:match("html$",process)
```

The `make4ht-filter` module return a function which can be used for the filter chain building. Multiple filters can be chained, each of them can modify the string which was modified by the previous filters. The changes are then saved to the processed file.

Built-in filters are:

cleanspan clean spurious span elements when accented characters are used

cleanspan-nat alternative clean span filter, provided by Nat Kuhn

fixligatures decompose ligatures to base characters

hruletohr `\hrule` commands are translated to series of underscore characters by `tex4ht`, this filter translate these underscores to `<hr>` elements

entites convert prohibited named entities to numeric entities (currently, only ` `, as it causes validation errors, and `tex4ht` is producing it sometimes)

fix-links replace colons in local links and id attributes with underscores. Some cross-reference commands may produce colons in internal links, which results in validation error.

mathjaxnode use `mathjax-node-page` to convert from MathML code to HTML + CSS or SVG. See the available settings.

odttemplate use styles from another ODT file serving as a template in the current document. It works for the `styles.xml` file in the ODT file. During the compilation, this file is named as `\jobname.4oy`.

staticsite create HTML files in format suitable for static site generators such as Jekyll

svg-height some SVG images produced by `dvipng` seem to have wrong dimensions. This filter tries to set the correct image size.

Function `filter` accepts also function arguments, in this case this function takes file contents as a parameter and modified contents are returned.

Example:

```
local filter = require "make4ht-filter"
local changea = function(s) return s:gsub("a","z") end
local process = filter{"cleanspan", "fixligatures", changea}
Make:htlatex()
Make:htlatex()
Make:match("html$",process)
```

In this example, spurious span elements are joined, ligatures are decomposed, and then all letters 'a' are replaced with 'z' letters.

3.2.2 DOM filters

DOM filters use the LuaXML library to modify directly the XML object. This enables more powerful operations than the regex based filters from the previous section.

Example:

```
local domfilter = require "make4ht-domfilter"  
local process = domfilter {"joincharacters"}  
Make:match("html$", process)
```

Available DOM filters:

aeneas Aeneas is a tool for automagical synchronization of text and audio. This filter modifies the HTML code to support the synchronization.

fixinlines put all inline elements which are direct children of the <body> elements to a paragraph.

idcolons replace the colon (:) character in internal links and id attributes. They cause validation issues.

joincharacters join consecutive or <mn> elements.

joincolors many elements with unique id attribute are created when \LaTeX colors are being used in the document. CSS rule is added for each of these elements, which may result in substantial grow of the CSS file. This filter replace these rules with a common one for elements with the same color value.

odtimagesize set correct dimensions for images in the ODT format. It is loaded by default for the ODT output.

t4htlinks fix hyperlinks in the ODT format.

3.2.3 make4ht-aeneas-config package

Companion for the aeneas DOM filter is the make4ht-aeneas-config plugin. It can be used to write Aeneas configuration file or execute Aeneas on the generated HTML files.

Available functions:

write_job(parameters) write Aenas job configuration to config.xml file. See the Aeneas documentation for more information about jobs.

execute(parameters) execute Aeneas.

process_files(parameters) process the audio and generated subtitle files.

By default, the `smil` file is created. It is assumed that there is audio file in `mp3` format named as the TeX file. It is possible to use different formats and file names using mapping.

The configuration options can be passed directly to the functions or set using `filter_settings "aeneas-config" {parameters}` function.

Available parameters:

lang document language. It is interfered from the HTML file, so it is not necessary to set it.

map mapping between HTML, audio and subtitle files. More info bellow.

text_type type of the input. The aeneas DOM filter produces unparsed text type.

id_sort sorting of id attributes. Default value is `numeric`.

id_regex regular expression to parse the id attributes.

sub_format generated subtitle format. Default `smil`.

Additional parameters for the job configuration file:

- `description`
- `prefix`
- `config_name`
- `keep_config`

It is possible to generate multiple HTML files from the LaTeX source. For example, `tex4ebook` generates separate file for each chapter or section. It is possible to set options for each HTML file, in particular names of the corresponding audio files. This mapping is done using `map` parameter.

Example:

```
filter_settings "aeneas-config" {
  map = {
    ["sampleli1.html"] = {audio_file="sample.mp3"},
    ["sample.html"] = false
  }
}
```

Table keys are the configured file names. It is necessary to insert them as `["filename.html"]`, because of Lua syntax rules.

This example maps audio file `sample.mp3` to a section subpage. The main HTML file, which may contain title and table of contents doesn't have a corresponding audio file.

Filenames of the sub files corresponds to the chapter numbers, so they are not stable when a new chapter is added. It is possible to request file names interfered from the chapter titles using the `sec-filename` option or `tex4ht`.

Available `map` options:

audio_file the corresponding audio file

sub_file name of the generated subtitle file

The following options are same as their counter-parts from the main parameters table and generally don't need to be set:

- prefix
- file_desc
- file_id
- text_type
- id_sort
- id_prefix
- sub_format

Full example:

```
local domfilter = require "make4ht-domfilter"
local aeneas_config = require "make4ht-aeneas-config"

filter_settings "aeneas-config" {
  map = {
    ["krecekli1.xhtml"] = {audio_file="krecek.mp3"},
    ["krecek.xhtml"] = false
  }
}

local process = domfilter {"aeneas"}
Make:match("html$", process)

if mode == "draft" then
  aeneas_config.process_files {}
else
  aeneas_config.execute {}
end
```

3.3 Image conversion

It is possible to convert parts of LaTeX input to pictures, it is used for example for math or diagrams in tex4ht.

These pictures are stored in a special dvi file, which can be processed by the dvi to image commands.

This conversion is normally configured in the env file, which is system dependent and which has a bit unintuitive syntax. This configuration is processed by the t4ht application and conversion commands are called for all pictures.

It is possible to disable t4ht image processing and configure image conversion in the build file:

```
Make:image("png$",  
"dvipng -bg Transparent -T tight -o ${output} -pp ${page} ${source}")
```

`Make:image` takes two parameters, pattern to match image name and action. Action can be either string template with conversion command, or function which takes a table with parameters as an argument.

There are three parameters:

- output - output image file name
- source - dvi file with the pictures
- page - page number of the converted image

3.4 The mode variable

There is global mode variable available in the build file. It contains contents of the `--mode` command line option. It can be used to run some commands conditionally. For example:

```
if mode == "draft" then  
  Make:htlatex{}  
else  
  Make:htlatex{}  
  Make:htlatex{}  
  Make:htlatex{}  
end
```

In this example (which is the default configuration used by `make4ht`), LaTeX is called only once when `make4ht` is called with `draft` mode:

```
make4ht -m draft filename
```

3.5 The settings table

You may want to access to the parameters also outside commands, file matches and image conversion functions. For example, if you want to convert your file to the OpenDocument Format (ODT), you can use the following settings, based on the `oolatex` command:

```
settings.tex4ht_sty_par = settings.tex4ht_sty_par ..",ooffice"  
settings.tex4ht_par = settings.tex4ht_par .. " ooffice/! -cmozhtf"  
settings.t4ht_par = settings.t4ht_par .. " -cooxtpipes -coo "
```

There are some functions to ease access to the settings:

`set_settings{parameters}` overwrite settings with values from a passed table

`settings_add{parameters}` add values to the current settings
`filter_settings "filter name" {parameters}` set settings for a filter
`get_filter_settings(name)` get settings for a filter

Using these functions, it is possible to simplify the settings for the ODT format:

```
settings_add {
  tex4ht_sty_par = ",ooffice",
  tex4ht_par = " ooffice/! -cmozhtf",
  t4ht_par = " -cooxtpipes -coo "
}
```

Settings for filters and extensions can be set using `filter_settings`:

```
filter_settings "test" {
  hello = "world"
}
```

These settings can be read in the extensions and filters using `get_filter_settings`:

```
function test(input)
  local options = get_filter_settings("test")
  print(options.hello)
  return input
end
```

3.6 List of available settings for filters and extensions.

These settings may be set using `filter_settings` function.

3.6.1 The tidy extension

options command line options for the tidy command. Default value is `-m -utf8 -w 512 -q`.

3.6.2 The fixinlines dom filter

inline_elements table of inline elements which shouldn't be direct descendants of the body element. The element names should be table keys, the values should be true.

Example

```
filter_settings "fixinlines" {inline_elements = {a = true, b = true}}
```

3.6.3 The joincharacters dom filter

charelements table of elements which should be joined if several instances with the same value of class attribute are side by side.

Example

```
filter_settings "joincharacters" { charclasses = { span=true, mn = true}}
```

3.6.4 The mathjaxnode filter

options command line options for the mpage command. Default value is `--output CommonHTML`

Example

```
filter_settings "mathjaxnode" {  
  options="--output SVG --font Neo-Euler"  
}
```

cssfilename mpage puts some CSS code into the HTML pages. mathjaxnode extracts this information and saves it to a standalone CSS file. Default CSS filename is `mathjax-ctml.css`

fontdir directory with MathJax font files. This option enables use of local fonts, which is usefull in Epub conversion, for example. The font directory should be sub-directory of the current directory. Only TeX font is supported at the moment.

Example

```
filter_settings "mathjaxnode" {  
  fontdir="fonts/TeX/woff/"  
}
```

3.6.5 The aeneas filter

skip_elements List of CSS selectors that match elements which shouldn't be processed. Default value: { "math", "svg"}.

id_prefix prefix used in the ID attribute forming.

sentence_match Lua pattern used to match a sentence. Default value: `"([%.^%?^!]*)([%.%?!]*)"`.

3.6.6 The staticsite filter and extension

site_root directory where generated files should be copied.

map table where keys are patterns that match filenames, value contains destination directory for matched files, relative to the site_root (it is possible to use .. to switch to parent directory).

file_pattern pattern used for filename generation. It is possible to use string templates and format strings for os.date function. Default value of %Y-%m-%d-\${input} creates names in the form of YYYY-MM-DD-file_name.

header table with variables to be set in the YAML header in HTML files. If the table value is a function, it is executed with current parameters and HTML page DOM object as arguments.

Example:

```
local outdir = os.getenv "blog_root"

filter_settings "staticsite" {
  site_root = outdir,
  map = {
    [".css$"] = "../css/"
  },
  header = {
    layout="post",
    date = function(parameters, dom)
      return os.date("!%Y-%m-%d %T", parameters.time)
    end
  }
}
```

3.6.7 The dvisvgm_hashes extension

options command line options for Dvisvgm. The default value is -n --exact -c 1.15,1.15.

cpu_cnt number of processor cores used for conversion. The extension tries to detect the available cores automatically by default.

parallel_size number of pages used in each Dvisvgm call. The extension detects changed pages in the DVI file and construct multiple calls to Dvisvgm with only changed pages.

scale SVG scaling.

3.6.8 The odttemplate filter and extension

template filename of the template ODT file

odttemplate can also get the template filename from the odttemplate option from tex4ht_sty_par parameter. It can be set using following command line call, for example:

```
make4ht -f odt+odttemplate filename.tex "odttemplate=template.odt"
```

4 Configuration file

It is possible to globally modify the build settings using the configuration file. New compilation commands can be added, extensions can be loaded or disabled and settings can be set.

4.1 Location

The configuration file can be saved either in \$HOME/.config/make4ht/config.lua or in .make4ht in the current directory or it's parents (up to \$HOME).

4.2 Additional commands

There are two additional commands:

Make:enable_extension(name) require extension

Make:disable_extension(name) disable extension

4.3 Example

The following configuration add support for the biber command, requires common_domfilters extension and requires MathML output for math.

```
Make:add("biber", "biber ${input}")
Make:enable_extension "common_domfilters"
settings_add {
  tex4ht_sty_par = ",mathml"
}
```

5 Command line options

make4ht - build system for tex4ht

Usage:

```
make4ht [options] filename ["tex4ht.sty op." "tex4ht op."
    "t4ht op" "latex op"]
```

-b,--backend (default tex4ht) Backend used for xml generation.

possible values: tex4ht or lua4ht

```
-c,--config (default xhtml) Custom config file
-d,--output-dir (default "") Output directory
-e,--build-file (default nil) If build file name is different
  than `filename`.mk4
-f,--format (default nil) Output file format
-l,--lua Use luatex for document compilation
-m,--mode (default default) Switch which can be used in the makefile
-n,--no-tex4ht Disable dvi file processing with tex4ht command
-s,--shell-escape Enables running external programs from LaTeX
-u,--utf8 For output documents in utf8 encoding
-v,--version Print version number
-x,--xetex Use xelatex for document compilation
<filename> (string) Input file name
```

You can still invoke make4ht in the same way as htlatex:

```
make4ht filename "customcfg, charset=utf-8" "--cunihtf -utf8" "-dfoo"
```

Note that this will not use make4ht routines for output directory making and copying. If you want to use them, change the line above to:

```
make4ht -d foo filename "customcfg, charset=utf-8" "--cunihtf -utf8"
```

This call has the same effect as the following:

```
make4ht -u -c customcfg -d foo filename
```

Output directory doesn't have to exist, it will be created automatically. Specified path can be relative to current directory, or absolute:

```
make4ht -d use/current/dir/ filename
make4ht -d ../gotoparentdir filename
make4ht -d ~/gotosomedir filename
make4ht -d c:\documents\windowpathsareworkingtoo filename
```

6 Troubleshooting

6.1 Incorrect handling of command line arguments for tex4ht, t4ht or latex

Sometimes, you may get a similar error:

```
make4ht:unrecognized parameter: i
```

It may be caused by a following make4ht invocation:

```
make4ht hello.tex "customcfg,charset=utf-8" "--cunihtf -utf8" -d foo
```

The command line option parser is confused by mixing options for `make4ht` and `tex4ht` in this case and tries to interpret the `-cunihtf -utf8`, which are options for `tex4ht` command as `make4ht` options. To fix that, you can either move the `-d foo` directly after `make4ht` command:

```
make4ht -d foo hello.tex "customcfg,charset=utf-8" "-cunihtf -utf8"
```

Another option is to add a space before `tex4ht` options:

```
make4ht hello.tex "customcfg,charset=utf-8" " -cunihtf -utf8" -d foo
```

The former way is preferable, though.

6.2 Filenames containing spaces

`tex4ht` cannot handle filenames containing spaces. `make4ht` thus replaces spaces in input file names with underscores, so generated XML files use underscores instead of spaces as well.

6.3 Filenames containing non-ASCII characters

The odt output doesn't support accented filenames, it is best to stick to ASCII characters in filenames.

7 License

Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3.

8 Changelog

- 2019/05/24
 - version 0.2g released
 - fixed failing `dvisvgm_hashes` extension on Windows.
- 2019/05/02
 - fixed infinite loop bug in the `dvisvgm_hashes` extension
- 2019/04/09
 - `make4ht-joincolors` fix: remove the hash character from the color name. This caused issues with colors specified in the hexadecimal format.

- 2019/04/02
 - dvisvgm_hashes fix: update also the lgfile.images table with generated filenames, in order to support tex4ebook
- 2019/04/01
 - fixed bug in dvisvgm_hashes extension: didn't check for table index existence in string concatenation
- 2019/03/21
 - version 0.2f released
- 2019/03/15
 - check for the image dimensions existence in the odtimagesize domfilter.
- 2019/03/13
 - don't use odtimagesize domfilter in the ODT format, the issue it fixes had been resolved in tex4ht.
- 2019/03/08
 - use %USERPROFILE for home dir search on Windows.
- 2019/01/28
 - added joincolors domfilter and join_colors extension. It can join CSS rules created for the LaTeX colors and update the HTML file.
- 2019/01/22
 - version 0.2e released
 - updated the odttemplate filter. It will use styles from the generated ODT file that haven't been present in the template file.
- 2019/01/10
 - version 0.2d released
- 2019/01/05
 - added docbook and tei output formats.
- 2018/12/19

- new library: `make4ht-xtpipes.lua`. It contains code for xtpipes handling.
 - moved Xtpipes handling code from `formats/odt.lua`.
- 2018/12/18
 - new filter: `odttemplate`. It can be used for replacing style in a generated ODT file by a style from another existing ODT file.
 - new extension: `odttemplate`. Companioning extension for filter with the same name.
 - fixed bug in `make4ht-filters.lua`: the `parameters` table haven't been passed to filters.
- 2018/12/17
 - fixed extension handling. The disabling from the command line didn't take precedence over extensions enabled in the config file. Extensions also could be executed multiple times.
- 2018/11/08
 - removed replacing newlines by blank strings in the `joincharacters` domfilter. The issue it fixed doesn't seem to exist anymore, and it ate spaces sometimes.
- 2018/11/01
 - added `t4htlinks` domfilter
 - fixed the xtpipes and filters execution order in the ODT format
- 2018/10/26
 - fixed ODT generation for files that contains special characters for Lua string patterns
 - replace non-breaking spaces with entities. It caused issues in LO
- 2018/10/18
 - fixed the executable installation
- 2018/09/16
 - added the `scale` option for `dvismgm_hashes` extension
- 2018/09/14
 - require the `-dvi` option with `latexmk_build` extension

- 2018/09/12
 - added xindy command for the build file
- 2018/09/03
 - expanded the --help option
- 2018/08/27
 - added odimagesize domfilter
 - load odimagesize by default in the ODT format
- 2018/08/23
 - released version 0.2c
- 2018/08/21
 - added processor core detection on Windows
 - make processor number configurable
 - updated the documentation.
- 2018/08/20
 - added dvisvgm_hashes extension
- 2018/07/03
 - create the mimetype file to achieve the ODT file validity
- 2018/07/02
 - disabled conversion of XML entities for &, < and > characters back to Unicode, because it breaks XML validity
- 2018/06/27
 - fixed root dir detection
- 2018/06/26
 - added code for detection of TeX distribution root for MikTeX and TL
- 2018/06/25
 - moved call to xtpipes from t4ht to the ODT format drives. This should fix issues with path expansion in tex4ht.env in TeX distributions.

- 2018/06/22
 - added `mkutils.find_zip` function. It detects zip or miktex-zip executables
- 2018/06/19
 - added new filter: `entities-to-unicode`. It converts XML entities for Unicode characters back to Unicode.
 - execute `entities-to-unicode` filter on text and math files in the ODT output.
- 2018/06/12
 - added support for direct ODT file packing
- 2018/06/11
 - new function available for formats, `format.modify_build`
 - function `mkutils.delete_dir` for directory removal
 - function `mkutils.mv` for file moving
 - started on packing of the ODT files directly by the format, instead of `t4ht`
- 2018/06/08
 - added support for filenames containing spaces
 - added support for filenames containing non-ascii characters
 - don't require sudo for the installation, let the user to install symbolic links to `$PATH`
- 2018/05/03
 - released version 0.2b
 - bug fix: use only load function in `Make:run`, in order to support a local environment.
- 2018/05/03
 - released version 0.2a
 - renamed `latexmk` extension to `latexmk_build`, due to clash in TL
- 2018/04/18
 - `staticsite` extension:
 - * make YAML header configurable

- * set the time and updated headers
 - don't override existing tables in filter_settings
- 2018/04/17
 - done first version of staticsite extension
- 2018/04/16
 - check for Git repo in the Makefile, don't run Git commands outside of repo
- 2018/04/15
 - added staticsite filter
 - working on staticsite extension
- 2018/04/13
 - use ipairs instead of pairs to traverse lists of images and image match functions
 - load extensions in the correct order
- 2018/04/09
 - released version 0.2
 - disabled default loading of common_domfilters extension
- 2018/04/06
 - added Make:enable_extension and Make:disable_extension functions
 - documented the configuration file
- 2018/03/09
 - load the configuration file before extensions
- 2018/03/02
 - Aeneas execution works
 - Aeneas documentation
 - added support for .make4ht configuration file
- 2018/02/28
 - Aeneas configuration file creation works

- 2018/02/22
 - fixed bug in fixinlines DOM filter
- 2018/02/21
 - added Aeneas domfilter
 - fixed bugs in joincharacters DOM filter
- 2018/02/20
 - fixed bug in joincharacters DOM filter
 - make woff default font format for mathjaxnode
 - added documentation for mathjaxnode settings
- 2018/02/19
 - fixed bug in filter loading
 - added mathjaxnode extension
- 2018/02/15
 - use HTML5 as a default format
 - use common_domfilters implicitly for the XHTML and HTML5 formats
- 2018/02/12
 - added common_domfilters extension
 - documented DOM filters
- 2018/02/12
 - handle XML parsing errors in the DOM handler
 - enable extension loading in Formatters
- 2018/02/11
 - fixed Tidy extension output to support LuaXML
 - fixed white space issues with joincharacters DOM filter
- 2018/02/09
 - fixed issues with the Mathjax filter
 - documented basic info about thd DOM filters
 - DOM filter optimalizations

- 2018/02/08
 - make Tidy extension configurable
 - documented filter settings
- 2018/02/07
 - added filter for Mathjax-node
- 2018/02/06
 - created DOM filter function
 - added DOM filter for spurious inlinine elements
- 2018/02/03
 - added settings handling functions
 - settings made available for extensions and filters
- 2017/12/08
 - fixed the mk4 build file loading when it is placed in the current working dir and another one with same filename somewhere in the TEXMF tree.
- 2017/11/10
 - Added new filter: `svg-height`. It tries to fix height of some of the images produced by `dvisvgm`
- 2017/10/06
 - Added support for output format selection. Supported formats are `xhtml`, `html5` and `odt`
 - Added support for extensions
- 2017/09/10
 - Added support for `Latexmk`
 - Added support of `math` library and `tonumber` function in the build files
- 2017/09/04
 - fixed bug caused by the previous change – the `-help` and `-version` didn't work
- 2017/08/22

- fixed the command line option parsing for tex4ht, t4ht and latex commands
 - various grammar and factual fixes in the documentation
- 2017/04/26
 - Released version v0.1c
- 2017/03/16
 - check for TeX capacity exceeded error in the L^AT_EX run.
- 2016/12/19
 - use full input name in tex_file variable. This should enable use of files without .tex extension.
- 2016/10/22
 - new command available in the build file: Make:add_file(filename). This enables filters and commands to register files to the output.
 - use ipairs instead of pairs for traversing files and executing filters. This should ensure correct order of executions.
- 2016/10/18
 - new filter: replace colons in id and href attributes with underscores
- 2016/01/11
 - fixed bug in loading documents with full path specified
- 2015/12/06 version 0.1b
 - modified lapp library to recognize --version and
 - added --help and --version command line options
- 2015/11/30
 - use kpse library for build file locating
- 2015/11/17
 - better -jobname handling
- 2015/09/23 version 0.1a
 - various documentation updates

- `mozhtf` profile for unicode output is used, this should prevent ligatures in the output files
- 2015/06/29 version 0.1
 - major README file update
- 2015/06/26
 - added Makefile
 - moved INSTALL instructions from README to INSTALL