

# schollatex

Print-ready teaching worksheets, the easy way

A small tag-based language for handouts and exercises,  
built on LuaLaTeX

G rard Dubard

Version 2.1

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>The one rule</b>	<b>3</b>
<b>3</b>	<b>Class options</b>	<b>4</b>
<b>4</b>	<b>Text attributes</b>	<b>4</b>
<b>5</b>	<b>Aliases and macros — the factoring tool</b>	<b>5</b>
<b>6</b>	<b>Tables</b>	<b>6</b>
<b>7</b>	<b>Images</b>	<b>6</b>
<b>8</b>	<b>Maths</b>	<b>6</b>
8.1	Sets, logic and relations . . . . .	7
8.2	Brackets and accents . . . . .	8
8.3	Limits with an arrow . . . . .	8
8.4	Operators with an index . . . . .	8
8.5	Functions and trigonometry . . . . .	9
8.6	Integrals . . . . .	9
8.7	Derivatives . . . . .	9
8.8	Maths blocks . . . . .	10
<b>9</b>	<b>Function studies</b>	<b>10</b>
9.1	The function object . . . . .	10
9.2	The table . . . . .	11
9.3	The graph . . . . .	11
<b>10</b>	<b>Lists</b>	<b>11</b>
<b>11</b>	<b>Boxes</b>	<b>12</b>
<b>12</b>	<b>Grid (named-area layout)</b>	<b>12</b>
<b>13</b>	<b>Block aliases</b>	<b>13</b>
<b>14</b>	<b>Control flow</b>	<b>13</b>
<b>15</b>	<b>Escapes</b>	<b>13</b>

<b>16 Security</b>	<b>14</b>
<b>17 Examples</b>	<b>14</b>
<b>18 Diagnostics</b>	<b>14</b>

# 1 Introduction

**scholatex** is a small markup language for producing print-ready teaching materials — worksheets, exercise sheets, handouts, short assessments — without writing LaTeX. It is not a general-purpose replacement for LaTeX; it is a focused, consistent little language for the documents a teacher actually makes: a few framed exercises, a table of results, a couple of simple formulas, an image or two, laid out cleanly on a page meant to be printed and handed out.

It compiles to LuaLaTeX, so the output has full LaTeX typesetting quality, but the syntax is meant to be read and edited in minutes by someone who does not know LaTeX: no `\begin{tabular}{|c|c|}`, no counting ampersands, no hunting for the package that draws a coloured box. A single tag syntax covers text, tables, images, simple maths, framed boxes, lists and full-page named-area layouts — the building blocks of a worksheet. **scholatex** is a *closed language*: the backslash is an ordinary character, so raw LaTeX commands in the body are typeset literally rather than executed. Everything a worksheet needs is expressed through tags, which keeps documents consistent and safe to share.

It is built for the people LaTeX usually loses: teachers preparing classroom materials, and anyone who wants a clean printable sheet without climbing the LaTeX learning curve.

You write a `.tex` file with a tiny, readable syntax between `\begin{document}` and `\end{document}`. At compile time the **scholatex** class reads that body, transpiles it to LaTeX, and typesets it. Nothing to install beyond a LuaLaTeX distribution.

```
% !TeX program = lualatex
\documentclass[margins=20, size=12, imgdir=IMG]{scholatex}
\begin{document}

<Navy b 18pt c>My first scholatex document

This is a normal paragraph. <b>{Bold}, <i>{italic}, <Red>{red}.

<box line:Navy fill:AliceBlue radius:3 title:{A framed note}>>{
Boxes, tables, images and maths all use the same tag syntax.
}

\end{document}
```

## 2 The one rule

Everything is a **tag**: `<attributes>` followed either by `{content}` (inline) or by a line that ends in `{` (a block). Attribute words follow a single case convention:

Form	Meaning	Examples
lowercase	a short keyword (style, alignment, skip)	b, i, c, 2tab
CamelCase	a CSS colour (151 of them)	Navy, SteelBlue, Crimson
UPPERCASE	a font name	DEJAVU SANS

The order of words inside a tag never matters — emission is always normalised (page break, then vertical skips, then alignment, then tabs, then styles).

### 3 Class options

Set in `\documentclass[...]{scholatex}`:

Option	Default	Meaning
<b>margins</b>	20	N (all sides) or {top,right,bottom,left} in mm
<b>font</b>	Latin Modern Roman	main text font
<b>mathfont</b>	Latin Modern Math	math font
<b>size</b>	11	base font size in pt
<b>imgdir</b>	img	folder(s) searched for bare image names; accepts a comma-separated list, e.g. {IMG, IMAGES/PNG}
<b>tabwidth</b>	8	width of one tab, in mm
<b>lineheight</b>	8	height of one explicit line skip (<line>, <Nlines>), in mm
<b>linespread</b>	1.0	overall line spacing (1.5 = one-and-a-half); tall maths never touches even at 1.0
<b>scriptscale</b>	100	scale (%) of up/down scripts
<b>padding</b>	2	inner padding (mm) between a box/grid-area frame and its content
<b>lang</b>	fr	decimal separator: <b>fr</b> (comma) or <b>en</b> (point); affects both literal decimals in maths and interpolated values
<b>untrusted</b>	false	when <b>true</b> , runs the document's Lua in a restricted sandbox (see §16)

Headings carry no extra vertical space of their own, and no built-in colour: to style a heading (colour, weight, size, or a line skip before it), fold a heading keyword into an alias and use it (see §5).

### 4 Text attributes

**Inline styles** — **b** bold, **i** italic, **u** underline, **emph**, **sf** sans-serif, **sc** small caps.

**Colours** — a colour is always one of the 151 CSS / svgnames colours, written in CamelCase: Navy, Red, Tomato, SteelBlue, ForestGreen, .... There is a single rule — no lowercase shortcuts — so the everyday colours are simply capitalised: Red, Blue, Green, Gray. These are exactly the colours xcolor provides under **svgnames**: the 147 CSS Color Module names plus the four X11 extras LightGoldenrod, LightSlateBlue, NavyBlue and VioletRed. Names are case-sensitive — write Seashell, not SeaShell. The README groups all 151 by family for browsing.

**Fonts and sizes** — a font name in CAPITALS (<DEJAVU SANS>{...}); sizes as Npt or Npx (<14pt>{...}).

**Alignment** — **l** left, **c** centre, **r** right, **j** justified (the same letters as table columns).

**Tabs and skips** (the number is always a prefix) — Ntab indents the first line by N tabs; vertical skips follow singular/plural agreement: **line** or **1line** skips one line, **2lines**, **3lines**, ... skip several. Bare **tab** = **1tab**.

**Scripts** — **upN** raises text by N mm (superscript-like), **downN** lowers it (subscript-like): **x<sup>up4</sup>{2}**, **H<sub>down2</sub>{2}**0.

**Page break** — `nextpage`.

**Section headings** — `section`, `subsection`, `subsubsection` give the three heading levels, numbered automatically:

```
<section>First topic
<subsection>A detail
<subsubsection>A finer point
```

renders as ‘1 First topic’, ‘1.1 A detail’, ‘1.1.1 A finer point’. By default the numbers are hierarchical; a counter keyword on a heading sets the style of that level on its own, with no inherited prefix: `num` (1, 2, 3), `roman` (i, ii), `ROMAN` (I, II), `alpha` (a, b), `ALPHA` (A, B). Thus `<section ROMAN>` with `<subsection num>` gives I, II and, under each, 1, 2 — not I.1. A heading can also be written as a **block** carrying a **title**: `option`, with its body in braces:

```
<subsection title:{A heading}>{
<tab>This body paragraph is indented on its first line.
}
```

A **table of contents** is printed with `<tableofcontents>`; give it a title in braces:

```
<tableofcontents>{Table of contents}
```

Combine anything in one tag:

```
<nextpage 2lines 2tab j Navy b>{A new page, a two-line skip, a two-tab
indent, justified, Navy, bold --- all before the first letter of the text.}
```

## 5 Aliases and macros — the factoring tool

This is what makes `scholatex scale`. Define a style **once**, at the top of the document, then name it everywhere instead of repeating its attributes. One edit at the definition restyles the whole document.

```
let title = <Navy b 18pt c>           % style alias
let h1    = <Navy b section>          % a heading style, reusable
let p     = <tab>                      % a standard indented paragraph
<title>My heading
<h1>First topic
<p>{ A paragraph, indented and justified, named not described. }

let n = 7                             % value, usable in #{...}
Seven squared is #{n*n}.

let greet{name} = Hello #name!        % text macro with parameters
```

Change `let h1 = <Navy b section>` to `<ForestGreen b section>` once and **every** first-level heading follows — the single point of control that keeps a long document consistent.

## 6 Tables

Columns are declared in brackets, **one two-letter placement code per column**. The first letter is vertical (**t** top, **m** middle, **b** bottom), the second horizontal (**l**, **c**, **r**). So **mc** is middle-centre, **br** bottom-right. Columns share the page equally; **N**: before the code fixes a width in mm (`[40:t1, 30:mc]`). Cells are separated by `|`, rows by line breaks, and `<nextline>` breaks a line inside a cell.

```
<table [mc, tl, br] borders header>{
Figure | Formula | Value
<img 25>{cat.png} | $1/2 + 1/3$ | $5/6$
}
```

**borders** draws rules; **header** bolds the first row. **gap:N** sets the horizontal spacing between columns, in mm.

A cell may span several columns with **colspan:N**, or several rows with **rowspan:N** ( $N \geq 2$ ). For a **rowspan**, each cell it covers on the lines below is marked with a lone `..`

```
<table [mc, ml, mc, mc] borders header gap:3>{
<colspan:4 mc>{Term report}
Day | Subject | Mark | Coef.
<rowspan:2 mc>{Monday} | Maths | 15 | 4
. | French | 12 | 3
}
```

Colour options act **inside** the table, on its cells and rules — **fill**: colours every body cell, **line**: the rules, **text**: the text colour, and **headerfill**: / **headertext**: the header row. These are not box options: a table has no **radius**:, **title**: or outer frame. To frame a table, wrap it in a `<box>`.

## 7 Images

```
<img>{chat.png}           % fills the available width (the cell or line)
<img 25>{chat.png}        % 25 mm wide
<img 25x15>{chat.png}     % fits a 25x15 mm box, ratio preserved
```

A bare name is searched in each folder of `imgdir` in turn, then at the project root. An explicit path always works, with or without `./`.

## 8 Maths

Wrap maths in `$...$`. A small mini-language keeps it light:

You write	You get
*	$\times$
+-	$\pm$
<= >= !=	$\leq \geq \neq$
a/b	fraction (chained a/b/c reads as (a/b)/c)
x^2 x_i	power / index (bind tighter than /)
sqrt(2)	$\sqrt{2}$
sum(i=1, n) i	$\sum$ with bounds, display style
prod(k=1, n) k	$\prod$ with bounds, display style
int(x) f(x)	$\int f(x) dx$ (differential added)
int(x=a, b) f(x)	$\int_a^b f(x) dx$
contourint(C) f(z)	$\oint$ contour integral
pview(x=a, b) f(x)	p.v. $\int$ principal value
meanint(x=a, b) f(x)	$\overline{\int}$ average integral
dy/dx, df/dx	derivative, upright d (ISO)
sin(x) cos(x) ln(x)	upright function names
abs(x)	$ x $
norm(v)	$\ v\ $
vec(AB)	$\overrightarrow{AB}$
floor(x) ceil(x)	$\lfloor x \rfloor \lceil x \rceil$
bar(z), conj(z)	$\bar{z}$ (conjugate, mean, closure)
not(A cup B)	$\overline{A \cup B}$ (logical negation)
lim(x->0) f(x)	limit, target under the word
partial, nabla	$\partial, \nabla$
pi, alpha, ...	Greek letters
inf	$\infty$

The helpers nest, so the secondary-school staples come for free: `norm(vec(AB))` is the norm of a vector, `vec(AB) + vec(BC) = vec(AC)` is Chasles' relation.

## 8.1 Sets, logic and relations

A worksheet from collège to the upper years needs more than arithmetic. The mini-language carries the standard notation as plain words and ASCII shortcuts, so a statement reads as one types it.

**Number sets** — a doubled capital gives the blackboard-bold set, the ASCII Math convention. Doubling avoids any clash with a one-letter variable: NN  $\mathbb{N}$ , ZZ  $\mathbb{Z}$ , DD  $\mathbb{D}$ , QQ  $\mathbb{Q}$ , RR  $\mathbb{R}$ , CC  $\mathbb{C}$ , plus PP KK HH FF EE UU for the advanced ones.

**Comparisons** — inside a formula, < > <= >= != give < >  $\leq \geq \neq$ . (In running prose, double the chevrons — «=» prints a literal  $\Leftrightarrow$ .)

**Quantifiers and logic** — forall  $\forall$ , exists  $\exists$ ; the connectives and  $\wedge$ , or  $\vee$ , lnot  $\neg$ , neg  $\neg$ . Implication and equivalence come both as words and as arrows: => or implies  $\Rightarrow$ , «=» or iff  $\Leftrightarrow$ . The longer arrow forms always win over the comparison they contain, so `abs(x) <= 1 <=> -1 <= x <= 1` reads correctly inside a formula.

**Negation** — a single rule: ! in front of a relation or quantifier negates it, choosing the proper struck-through glyph. So !in is  $\notin$ , !exists is  $\nexists$ , !subset is  $\not\subset$ , !subseteq is  $\not\subseteq$ , !equiv is  $\neq$ . (!= stays “not equal”,  $\neq$ .)

**Set relations** — in  $\in$ , subset  $\subset$ , supset  $\supset$ , subseteq  $\subseteq$ , supseteq  $\supseteq$ , cup  $\cup$ , cap  $\cap$ , setminus



`\`, `emptyset`  $\emptyset$  (negate any of them with `!`).

**Arrows** — `->` or `to`  $\rightarrow$ , `mapsto`  $\mapsto$ .

```
$forall epsilon > 0, exists eta > 0$
$x in RR setminus QQ$
$x !in QQ$
$(P and Q) => P$
```

## 8.2 Brackets and accents

The integer part and a few one-argument wrappers follow the same `name(...)` shape as `abs` and `vec`: `floor(x)`  $\lfloor x \rfloor$ , `ceil(x)`  $\lceil x \rceil$ , `set(x : x > 0)` a brace set, `abr(u, v)`  $\langle u, v \rangle$  an inner product.

An overline is named by intent, the same rule under two words: `bar(...)` for the generic bar (complex conjugate, mean, closure of a set) and `not(...)` for logical negation — so `bar(z)` is  $\bar{z}$  and `not(A cup B)` is  $\overline{A \cup B}$ . The usual accents complete the set: `hat(f)`  $\hat{f}$ , `tilde(x)`  $\tilde{x}$ .

## 8.3 Limits with an arrow

`lim(x->0) f(x)` already sets a limit with its target under the word. For the running phrase “ $u_n$  tends to  $\ell$ ” written over an arrow, use `arrow(...)`: `u_n arrow(n to +inf) l` sets a long right arrow with the condition underneath. `to` and `->` are interchangeable inside it.

```
$lim(n -> +inf) u_n = l$
$u_n arrow(n to +inf) l$
```

Scripts bind tighter than division, as in ordinary reading:  $x^2/y$  is the fraction  $\frac{x^2}{y}$  and  $1/i^2$  is  $\frac{1}{i^2}$ , not  $\frac{1^2}{i}$ . To divide by a base before its script, parenthesise.

## 8.4 Operators with an index

`sum`, `prod` and `lim` carry their index in `(...)` and set their whole expression in display style, so a fraction in the body keeps full size and a limit’s target sits *under* the word, as on a blackboard. A `sum/prod/lim` body runs to the end of the formula or to the first `=`, so the right-hand side of an identity stays outside the operator:

```
$sum(i=1, n) i = n(n+1)/2$
$lim(x->0) sin(x)/x = 1$
$lim(x->+inf) 1/x$
```

## 8.5 Functions and trigonometry

Function names are set upright automatically — no backslashes: `sin cos tan cot sec csc`, the inverses `arcsin arccos arctan`, the hyperbolics `sinh cosh tanh coth`, and `ln log exp det dim gcd deg ker arg max min sup`. A name glued to `(...)` takes its argument as one atom, so fractions and powers behave:

```
$sin(x)^2 + cos(x)^2 = 1$  
$tan(x) = sin(x)/cos(x)$
```

## 8.6 Integrals

The integral family names its variable and bounds in the head `(...)` and captures the integrand as its body; the differential is appended for you. No bounds gives a primitive, a comma-separated pair a definite integral:

```
$int(x) f(x)$           % primitive  
$int(x=a, b) f(x)$      % definite
```

Separate several domains with `;` for multiple integrals: the count of domains chooses  $\int$ ,  $\iint$  or  $\iiint$ , and the differentials come out in reverse order (the Fubini convention). A single named domain is a region integral:

```
$int(x=a, b ; y=c, d) f(x,y)$  
$int(D) f$
```

Three named integrals complete the family: `contourint(C) f(z)` a contour integral  $\oint$ , `puint(x=a, b) f(x)` a Cauchy principal value, and `meanint(x=a, b) f(x)` the average (normalised) integral.

## 8.7 Derivatives

A Leibniz derivative is written as the fraction it is, and the differential `d` is set upright (ISO 80000-2), matching the `d` of the integrals. The romanisation triggers *only* when both sides of the fraction carry the differential, so a variable named `d` is never disturbed: `d/2` stays the fraction `d` over 2.

```
$dy/dx$                 % upright d  
$(d^2 y)/(dx^2)$        % second derivative  
$dy/dx + y = 0$         % differential equation
```

Partial derivatives use `partial` ( $\partial$ ); parenthesise each side so the fraction groups correctly:

```
$(\partial f)/(\partial x)$  
$(\partial u)/(\partial t) = (\partial^2 u)/(\partial x^2)$
```

Inject a computed value with `#{expr}` (or `#name`), including inside maths: `$$k^2$`. Decimal numbers follow the `lang` option.

## 8.8 Maths blocks

Matrices and systems are blocks: **one line is one row**, and inside a matrix `;` separates the entries.

```
<matrix>{  
1 ; 2 ; 3  
4 ; 5 ; 6  
}
```

`<matrix>` draws parentheses, `<det>` the vertical bars of a determinant, `<bmatrix>` square brackets. A single `|` inside a row draws the separation bar of an **augmented matrix**, at the column where you type it; it is allowed on `matrix` and `bmatrix`, never on `det`:

```
<bmatrix>{  
2 ; 1 | 7  
1 ; -1 | 1  
}
```

A `<system>` stacks equations under a brace and aligns them on the first relational operator:

```
<system>{  
2x + 3y = 7  
x - y = 1  
}
```

## 9 Function studies

Three tags turn a function into a variation table and a curve. They share one source of truth: a *function object* built once with `<fn>`, then read by `<varstab>` (the table) and `<plot>` (the graph).

### 9.1 The function object

```
let k = <fn name:{k(x)}  
      expr:{(x^2+1)/(x-1)}  
      x:{-inf | 1-sqrt(2) | 1 | 1+sqrt(2) | +inf}
```

```
second:{- | - || + | +}
deriv:{+ | - || - | +}
var:{-inf / 2-2sqrt(2) \ -inf || +inf \ 2+2sqrt(2) / +inf}>
```

`let NAME = <fn ...>` stores the object under NAME (the assignment may span several lines, up to the closing `>`). The fields are **name**: (function and variable, fixing the row labels), **expr**: (the formula, read only by `<plot>`), **x**: (remarkable abscissas separated by `|`), **deriv**: and **second**: (sign of the first and second derivative, one per interval), and **var**: (the variation line).

## 9.2 The table

`<vartab k>` reads the object; or write the data inline with `<vartab x:{...} deriv:{...} var:{...}>`. Only **x**: and **var**: are required, so the table comes in four shapes:

- **second**: + **deriv**: — full study:  $x, f''(x), f'(x), f(x)$
- **deriv**: — classic variation table:  $x, f'(x), f(x)$
- **second**: — convexity table:  $x, f''(x), f(x)$
- neither — plain value table:  $x, f(x)$

Sign lines take one sign per interval (+, -, or empty); `||` marks a forbidden value and crosses every row; zeros at sign changes are placed automatically. In **var**:, a connector is `/` (rising) or `\` (falling) *surrounded by spaces* — glued, as in  $2/3$ , it is a fraction. A value between two arrows of the same direction is rejected: the table lists only bounds and extrema.

## 9.3 The graph

```
<plot k samples:200 x:{-4, 6} y:{-10, 12}>
```

`<plot k>` reads **expr**: and **name**: from the object. **x**:{**a**, **b**} is the horizontal display window (defaults to the table's finite abscissas), **y**:{**c**, **d**} the vertical window (needed when the function runs to infinity), **samples**:*N* the number of points. The formula is translated to the plotter's syntax (variable renamed, trigonometry in degrees, implicit products made explicit) and poles are handled so no spurious line joins the branches. Supported in **expr**:: + - \* / ^, parentheses, `sin cos tan exp ln log sqrt abs`, and `pi`.

`<vartab>` is declarative, `<plot>` is computed: keeping **var**: consistent with **expr**: is the author's responsibility.

## 10 Lists

`<list:STYLE>{ ... }` makes a list; the style is required and comes right after the name. One item per non-empty line — no item tag. A `<list:...>` written under an item becomes its sub-list, nested as deep as you like.

```

<list:disc>{
Fruits
<list:circle>{
apples
pears
}
Vegetables
}

```

Styles — bullets: `none disc circle square`; numbered: `decimal alpha ALPHA roman ROMAN` (the case of the keyword sets the case of the letters); checkboxes: `check`.

## 11 Boxes

```

<box line:Crimson fill:MistyRose radius:4 title:{A note}>{
Content here.
}

```

Options: `line`: frame colour, `fill`: background, `text`: text colour, `radius:N` rounded corners (mm), `width:N` or `width:N%`, `boxrule:N`, `boxsep:N`, `break:yes` (allow page breaks), `title:{...}`, `titlefill:`, `titletext:.` A line containing only `--` splits a box into an upper and a lower region.

`<row gap:N>{ ... }` lays its child boxes side by side, with equal widths and equalised heights. A row accepts only `<box>` children.

A box also takes a **two-letter placement code** (`tl tc tr ml mc mr bl bc br`, default `tl`) that positions its content; the vertical part needs a `height`: to have room to act.

## 12 Grid (named-area layout)

For full-page layouts, `<grid>` borrows CSS Grid's named-area idea. A `template:[ ...]` of quoted rows draws the layout; each word names the cell at that position. A name repeated **horizontally** spans columns; repeated **vertically** it spans rows. A dot `.` is an empty cell. Each name must form a solid rectangle.

```

<grid template:[
  "title title logo"
  "intro info logo"
  "body body body"
] gap:4>{
  <area title>{ <Red b 16pt>Maths assessment }
  <area logo >{ <img>{blason.png} }
  <area intro>{ Instructions: no calculator. }
  <area info >{ Name: <nextline> First name: }
  <area body line:Navy fill:AliceBlue radius:2 title:{Exercise 1}>{
    Solve the equation...
  }
}

```

An area can be framed like a box by giving it the same options (`line:`, `fill:`, `radius:`, `title:`). An area with no options stays invisible (a bare cell). The grid itself takes `width:` (a percentage of the text width or a millimetre value) and `height:` (a millimetre value fixing the total height).

## 13 Block aliases

Define a reusable component once; `#param` placeholders are filled at the call site, and the call-site body becomes the block content.

```
let card{title, frame} = <box title:{#title} line:#frame radius:2>

<card First, Crimson>{
  Called with two arguments. No box options to repeat.
}
<card Second, Navy>{
  Same component, different look.
}
```

## 14 Control flow

```
for n in 1..3 {           % numeric range
  <c Navy b>Sheet #n
}

for f in [chat.png, chien.png] { % explicit list
  <img 16>{#f}
}

if score >= 10 {
  <Green>Passed.
} else {
  <Red>Try again.
}
```

Loops and conditions work in the document body, inside boxes, and inside table bodies. The loop variable interpolates everywhere via `#`.

## 15 Escapes

To print a character that `scholatex` treats specially, double it: `< >` give a literal `< >`, `{ { }` a literal `{ }`, and `##` a literal `#`. A backslash `\` is an ordinary character — write it as itself, so a Windows path like `C:\Users` just works. The characters `_` `tg_` `&` `%` `~` are escaped automatically. `%` `~` `^` are escaped automatically.

Braces carry structure (they delimit blocks and groups), so a *literal* brace must be **balanced**: write the pair `{ { ... } }` to print `{ ... }`. A lone, unmatched `{ { }` or `}` is reported as an unbalanced brace naming its line, rather than silently swallowing the rest of the document — so set-builder notation like `{ { x : x > 0 } }` is written as a pair and prints as one. Angle brackets and hashes have no such constraint; only braces need to balance.

A line break is the tag `<nextline>`; it works in running text and inside table cells. In ordinary text a blank line already starts a new paragraph, so `<nextline>` is only needed for a break *without* a paragraph change.

A line whose first non-space character is `%` is a **comment** and is dropped. A bare `#` not followed by a name or `{...}` is a literal `#`: only `#name` and `#{expr}` interpolate.

## 16 Security

scholatex evaluates `let name = expr, #{expr}` and the conditions of `for/if/while` as Lua at compile time, so by default a document can run arbitrary code — exactly like `\directlua`.

Setting `untrusted=true` runs that Lua in a restricted environment: only pure, side-effect-free names are visible (the maths the document needs plus `string/table` helpers), while `os`, `io`, `package`, `require`, `load`, `debug`, `setmetatable` and `getmetatable` are absent. A blocked access stops the compile with a clear message; a runaway loop is aborted by an instruction-count ceiling. Because the step counter cannot interrupt work inside a single C call, `string.rep` and `string.format` are capped — both through the global `string` table and through method calls on a string value `(("x"):rep(n))`, which a restricted string metatable routes to the same capped functions.

**Scope.** `untrusted` hardens the scholatex expression layer only. It does *not* sandbox LuaLaTeX as a whole: a hostile `.tex` can still call `\directlua`, `\write18` (with shell-escape), `\input`, and so on. To compile a whole `.tex` you do not trust, run `lualatex` **without** `-shell-escape`, ideally inside a container.

## 17 Examples

The `examples/` folder contains six self-contained, fully commented documents that together exercise every feature:

File	Covers
<code>text-style.tex</code>	case rule, styles, colours, fonts, sizes, alignment, escapes, aliases, TOC
<code>containers.tex</code>	tables, boxes and the named-area grid
<code>math-language.tex</code>	mini-language, sets, logic, negation, integer part, the overline
<code>math-analysis.tex</code>	operators, limits, trigonometry, derivatives, integrals
<code>math-algebra.tex</code>	matrix, determinant, augmented matrix, systems
<code>functions.tex</code>	full function studies with variation tables and plots

Compile any of them with `lualatex <file>.tex` from the `examples/` folder. The image folders `IMG/` and `IMAGES/PNG/` ship alongside them; `containers.tex` uses `imgdir={IMG, IMAGES/PNG}` to show that bare image names are resolved across several directories.

## 18 Diagnostics

Errors point at the source line, e.g. `scholatex: line 12: unknown tag attribute: 'xyz'`. Defining an alias whose name is a built-in (`let section = ..., let tab = ...`) prints a warning: the built-in always wins, so the alias would be silently dead — pick a different name.